

N276DA XLAUTOMATIC DOWN FEED
BAJADA AUTOMÁTICA

ART.	CODE / CÓDIGO
N276DA XL	8.48.80.71

PATENTED

VIDEO

TECHNICAL FEATURES

- Blade height 27 mm
- Hydraulic control system for automatic down feed
- Automatic or manual function
- Adjustable left cutting angle from 0° to 60° equipped with quick stop device at 45° and 60° positions
- Blade tensioner with indicator lamp and safety microswitch for proper blade integrity and tensioning

STANDARD EQUIPMENT

- Adjustable bar stop-rod for mass-produced cuts (L=600 mm)
- Steel column with built-in tool-holder
- Column in assembly kit

CARACTERÍSTICAS TÉCNICAS

- Altura hoja 27 mm
- Sistema hidráulico de control de bajada automática
- Funcionamiento automático o manual
- Ángulo de corte regulable de 0° a 60° izquierda, con dispositivo de bloqueo rápido en las posiciones 45° y 60°
- Tensor de hoja con indicador luminoso y microinterruptor de seguridad para garantizar tensado de la hoja correcto

EQUIPAMIENTO DE SERIE

- Varilla de sujeción del material regulable para realizar cortes en serie (L=600 mm)
- Base de acero, con espacio porta-objetos integrado
- Base in kit de montaje



GREAT CUTTING CAPACITY Ø 255 mm!!!
GRAN CAPACIDAD DE CORTE Ø 255 mm!!!



- Cast iron arm for a great strength (total weight 305 kg).
- Brazo de hierro fundido de gran robustez (peso total 305 kg).

CUTTING CAPACITY / CAPACIDAD DE CORTE			
0°	265x200 mm	255 mm	200x200 mm
45°	200x160 mm	175 mm	170x170 mm
60°	115x100 mm	110 mm	100x100 mm



- Hydraulic control system for automatic down feed.
- Sistema hidráulico de control de bajada automática.

KILOWATT	mm	Z/1"	M/min	WATT	a x b x h mm	Kg
1,0/1,3	2565x27x0,9	8/12*	35/70	60	1410x870x1650	311

*Standard bimetal cobalt blade / De serie hoja bimetálica al cobalto • 400 Volt - Hz 50 three-phase motor / Motor trifásico 400 Volt - Hz 50