

ABS 105**ABS**
Automatic Blade System

ART.	CODE / CÓDIGO
ABS 105	8.48.46.81

PATENTED

VIDEO

TECHNICAL FEATURES

- Push-click: 4 down feed speeds with mechanical selector
- Automatic cut-off switch after finishing cutting operation
- Safety emergency button to stop cutting
- Energy saving 100% motor efficiency is granted by the exclusive ABS system
- Maximum cutting versatility on all metal materials
- More than 10% saving on blade consumption

STANDARD EQUIPMENT

- Adjustable bar stop-rod for mass-produced cuts (L=500 mm).
- Blade cleaning felt spares kit
- Filter-circuit for electromagnetic interference damping according to rules in force

CARACTERÍSTICAS TÉCNICAS

- Push-click 4 velocidades de corte, con selector mecánico
- Interruptor de parada automática al final del corte
- Botón de seguridad para detener el corte
- El exclusivo sistema abs asegura el 100% del rendimiento del motor
- Máxima versatilidad de corte sobre todo tipo de metal
- Más del 10% de ahorro en el consumo de la hoja de sierra

EQUIPEMENTS DE SÉRIE

- Varilla de sujeción de la barra regulable, para realizar cortes en serie (L=500 mm)
- Kit de recambio filtro de limpieza de la hoja
- Circuito-filtro para la eliminación de interferencias electromagnéticas conforme con las normativas vigentes



MAX 105 mm

**WITHOUT LUBRICATION
SIN LUBRICACION****CUTTING CAPACITY / CAPACIDAD DE CORTE**

0°	100x85 mm	105 mm	95x95 mm
45°	65x60 mm	65 mm	65x65 mm

FULLY AUTONOMOUS CUTTING CYCLE WITHOUT OPERATOR / CICLO DE CORTE COMPLETAMENTE AUTÓNOMO, SIN PRESENCIA DEL OPERARIO**ABS**
Automatic Blade System

- Cut start up
- Puesta en marcha del corte



- Autonomous cutting cycle
- Ciclo de corte autónomo



- Automatic switch off
- Parada automática



950




1335x13x0,65



8/12*



60/80



730x390x500



17

*Standard bimetal cobalt blade / De serie hoja bimetálica al cobalto • 230 Volt - Hz 50 single-phase motor / Motor monofásico 230 Volt - Hz 50